


Multilayer Chip Ceramic Inductor –SDCL0402H –T01 Series



Operating Temp ◆ -55°C ~+125°C

Features


- ◆ Monolithic structure for high reliability
- ◆ High self-resonant frequency
- ◆ Excellent solderability and high heat resistance
- ◆ High Q factor

Applications ◆ RF circuit in telecommunication and other equipments

Product Identification

1 SDCL	2 0402	3 H	4 3N0	5 B	6 T	7 01																			
1 Type <table><tr><td>SDCL</td><td>Chip Ceramic Inductor</td></tr></table>		SDCL	Chip Ceramic Inductor	2 External Dimensions (L×W) (mm) <table><tr><td>0402 [01005]</td><td>0.4×0.2</td></tr></table>		0402 [01005]	0.4×0.2	3 Characteristics Code <table><tr><td>H</td></tr></table>			H														
SDCL	Chip Ceramic Inductor																								
0402 [01005]	0.4×0.2																								
H																									
4 Nominal Inductance <table><tr><td>Example</td><td>Nominal Value</td></tr><tr><td>3N0</td><td>3.0nH</td></tr><tr><td>16N</td><td>16nH</td></tr><tr><td colspan="2">※R=decimal point, N=nH</td></tr></table>		Example	Nominal Value	3N0	3.0nH	16N	16nH	※R=decimal point, N=nH		5 Inductance Tolerance <table><tr><td>B</td><td>±0.1nH</td></tr><tr><td>C</td><td>±0.2nH</td></tr><tr><td>S</td><td>±0.3nH</td></tr><tr><td>H</td><td>±3%</td></tr><tr><td>J</td><td>±5%</td></tr></table>		B	±0.1nH	C	±0.2nH	S	±0.3nH	H	±3%	J	±5%	6 Packing <table><tr><td>T</td><td>Tape & Reel</td></tr></table>		T	Tape & Reel
Example	Nominal Value																								
3N0	3.0nH																								
16N	16nH																								
※R=decimal point, N=nH																									
B	±0.1nH																								
C	±0.2nH																								
S	±0.3nH																								
H	±3%																								
J	±5%																								
T	Tape & Reel																								
		7 Serial Code <table><tr><td>01</td></tr></table>					01																		
01																									

Shape and Dimensions



Unit: mm [inch]

Type	L	W	T	a
SDCL0402H-01 [01005]	0.4±0.02 [.016±.0008]	0.2±0.02 [.008±.0008]	0.2±0.02 [.008±.0008]	0.095±0.025 [.0037±.0010]

Specifications

SDCL0402H-T01 Series

Part Number	Inductance	Min. Quality Factor	L, Q Test Freq.	Typical Q @ Freq. (GHz)					Min. Self-resonant Frequency	Max. DC Resistance	Max. Rated Current
				0.5	0.8	1.8	2.0	2.4			
Units	nH	-	MHz	-					MHz	Ω	mA
Symbol	L	Q	Freq.	Q					S.R.F	DCR	I _r
SDCL0402H0N2 □ T01	0.2	-	500	12	16	22	26	38	13000	0.4	320
SDCL0402H0N3 □ T01	0.3	-	500	12	15	22	25	36	13000	0.4	320
SDCL0402H0N4 □ T01	0.4	8	500	11	14	21	22	24	13000	0.4	320
SDCL0402H0N5 □ T01	0.5	8	500	10	13	21	23	25	13000	0.4	320
SDCL0402H0N6 □ T01	0.6	8	500	12	14	20	23	25	13000	0.4	320
SDCL0402H0N7 □ T01	0.7	8	500	11	13	21	22	24	13000	0.4	320
SDCL0402H0N8 □ T01	0.8	8	500	10	12	20	21	23	13000	0.4	320
SDCL0402H0N9 □ T01	0.9	8	500	11	13	20	22	24	13000	0.4	320
SDCL0402H1N0 □ T01	1.0	8	500	10	12	19	21	23	11500	0.4	220
SDCL0402H1N1 □ T01	1.1	8	500	11	13	19	22	24	11500	0.4	220
SDCL0402H1N2 □ T01	1.2	8	500	10	12	20	21	23	11500	0.4	220
SDCL0402H1N3 □ T01	1.3	8	500	10	12	19	21	23	11500	0.4	220
SDCL0402H1N4 □ T01	1.4	8	500	11	13	20	21	23	11500	0.4	220
SDCL0402H1N5 □ T01	1.5	8	500	10	13	19	21	24	11500	0.4	220
SDCL0402H1N6 □ T01	1.6	8	500	10	12	19	21	23	11500	0.4	220
SDCL0402H1N7 □ T01	1.7	8	500	11	13	20	21	24	9500	0.5	200
SDCL0402H1N8 □ T01	1.8	8	500	10	12	19	21	23	9000	0.5	200
SDCL0402H1N9 □ T01	1.9	8	500	10	12	20	21	23	9000	0.5	200
SDCL0402H2N0 □ T01	2.0	8	500	11	12	19	21	23	9000	0.5	200
SDCL0402H2N1 □ T01	2.1	8	500	10	12	19	22	24	9000	0.5	200
SDCL0402H2N2 □ T01	2.2	8	500	9.5	11	18	20	22	7500	0.55	200
SDCL0402H2N3 □ T01	2.3	8	500	10	12	19	21	23	7500	0.55	200
SDCL0402H2N4 □ T01	2.4	8	500	10	12	19	21	23	7500	0.55	200
SDCL0402H2N5 □ T01	2.5	8	500	9.5	11	18	20	22	7500	0.6	200
SDCL0402H2N6 □ T01	2.6	8	500	11	12	19	21	23	7500	0.6	200
SDCL0402H2N7 □ T01	2.7	8	500	10	12	19	22	24	7500	0.6	200
SDCL0402H2N8 □ T01	2.8	8	500	10	12	19	21	23	7500	0.8	200
SDCL0402H2N9 □ T01	2.9	8	500	10	12	19	21	23	7500	0.8	200
SDCL0402H3N0 □ T01	3.0	8	500	10	12	19	20	23	7500	0.9	200
SDCL0402H3N1 □ T01	3.1	8	500	10	13	19	20	22	7500	0.9	200
SDCL0402H3N2 □ T01	3.2	8	500	9	11	19	20	22	7500	0.9	180
SDCL0402H3N3 □ T01	3.3	8	500	10	13	19	20	23	7500	0.9	180
SDCL0402H3N4 □ T01	3.4	8	500	10	12	19	21	23	7500	1.0	180
SDCL0402H3N5 □ T01	3.5	8	500	10	13	19	21	24	7500	1.0	180
SDCL0402H3N6 □ T01	3.6	8	500	11	12	19	21	23	7500	1.0	180
SDCL0402H3N7 □ T01	3.7	8	500	10	12	19	21	23	7500	1.0	180
SDCL0402H3N8 □ T01	3.8	8	500	10	12	19	21	23	7500	1.0	180
SDCL0402H3N9 □ T01	3.9	8	500	9	11	19	20	22	7500	1.0	180
SDCL0402H4N0 □ T01	4.0	8	500	10	12	19	21	23	7500	1.1	180
SDCL0402H4N1 □ T01	4.1	8	500	11	12	19	21	24	7500	1.1	180
SDCL0402H4N2 □ T01	4.2	8	500	10	12	18	20	22	7500	1.1	180
SDCL0402H4N3 □ T01	4.3	8	500	10	13	19	21	24	7500	1.1	180
SDCL0402H4N7 □ T01	4.7	8	500	9	11	19	20	22	6500	1.2	160
SDCL0402H5N1 □ T01	5.1	8	500	10	12	18	19	22	6500	1.3	160
SDCL0402H5N6 □ T01	5.6	8	500	10	12	17	22	24	6000	1.5	140
SDCL0402H6N2 □ T01	6.2	8	500	10	11	18	20	23	5500	1.6	140
SDCL0402H6N8 □ T01	6.8	8	500	10	11	17	20	23	5500	1.8	140
SDCL0402H7N5 □ T01	7.5	8	500	10	13	17	22	24	4500	1.8	140
SDCL0402H8N2 □ T01	8.2	8	500	10	12	18	20	22	4500	2.0	140

Specifications

SDCL0402H-T01 Series


Part Number	Inductance	Min. Quality Factor	L, Q Test Freq.	Typical Q @ Freq. (GHz)					Min. Self-resonant Frequency	Max. DC Resistance	Max. Rated Current
				0.5	0.8	1.8	2.0	2.4			
Units	nH	-	MHz	-					MHz	Ω	mA
Symbol	L	Q	Freq.	Q					S.R.F	DCR	I _r
SDCL0402H9N1 □ T01	9.1	8	500	10	13	17	21	23	4000	2.0	140
SDCL0402H10N □ T01	10	8	500	9	12	18	20	21	4000	2.2	140
SDCL0402H11N □ T01	11	8	500	9	12	18	19	20	4000	2.4	140
SDCL0402H12N □ T01	12	8	500	9	12	17	18	18	4000	2.4	140
SDCL0402H13N □ T01	13	7	500	8	12	17	18	18	3500	3.0	140
SDCL0402H15N □ T01	15	7	500	8	12	16	15	14	3000	3.0	140
SDCL0402H16N □ T01	16	7	500	8	11	13	12	11	2500	3.2	140
SDCL0402H18N □ T01	18	7	500	7.5	10	12	10	9	2500	3.2	140
SDCL0402H20N □ T01	20	6	500	7	9	11	9	7	2500	4.5	120
SDCL0402H22N □ T01	22	6	500	7	10	10	9	7	2300	5.0	120
SDCL0402H24N □ T01	24	6	500	8	11	10	9	6	2000	5.5	120
SDCL0402H27N □ T01	27	6	500	8	10	8	7	-	2000	5.5	120
SDCL0402H30N □ T01	30	6	500	7	9	7	-	-	1800	6.5	90
SDCL0402H33N □ T01	33	6	300	8	9	7	-	-	1800	6.5	90

※ □ : Please specify the inductance tolerance. For L≤4.2nH, choose B=±0.1nH, C=±0.2nH or S=±0.3nH; For L≥4.3nH, choose H=±3%, J=±5%.
 ※: Please refer to "Measurement Notice For RF Inductors".

Typical Electrical Characteristics

SDCL0402H-T01 Series

Inductance vs. Frequency Characteristics



Q vs. Frequency Characteristics

